

STERLING 2™ SEATING

Operating Instructions

High Back Managerial and Low Back Task Models
with Synchronous Mechanism

P.O. Box 8400

Green Bay, WI 54308-8400

Tel 920.468.8100 • Fax 920.468.2633

©OEI 2007 Litho in USA Code OE-60860/VL407

Deriving Maximum Benefits From Your Sterling 2 High Back Managerial And Low Back Task Models With Synchronous Mechanisms

A. Tilt Lock (Left Side of Chair) 5 Positions

To engage lock, rotate handle rearward. To disengage lock, rotate handle forward then lean back into chair to release tilt lock feature.

B. Seat Height Adjustment

To lower seat height, pull the paddle toward the seat while seated in the chair. To raise the seat, lift body weight slightly off chair while pulling the paddle toward the seat. Release paddle to lock in position.

C. Pull-Out Telescoping Knob (Right Side of Chair)

To increase tension rotate knob forward (clockwise). To decrease tension rotate knob rearward (counter clockwise).

D. Back Height Adjustment

To adjust back height, grasp chair back and lift to desired height. The back will lock at each click stop. To lower back, simply raise above last click stop, disengaging the ratchet mechanism, and lower back to lowest position. Raise back height to desired position.

Fully Adjustable Arm Option

E. Arm Width Adjustment

To adjust arm width, pull up on lever moving arm horizontally in or out to one of three adjustment settings. Release lever to lock in place.

F. Arm Height Adjustment

To adjust arm height, pull up on button located at the top of the arm assembly. Raise or lower arm to the desired height and release lever to lock in position.

