

STERLING 2™ SEATING

Operating Instructions

Low Back Managerial with
Intensive Use Mechanism

P.O. Box 8400

Green Bay, WI 54308-8400

Tel 920.468.8100 • Fax 920.468.2633

©OEI 2007 Litho in USA Code OE-60860R1/VL407

Deriving Maximum Benefits From Your Sterling 2 Low Back Managerial Chair with Intensive Use Mechanism

A. Seat Tilt Adjustment

To release lock function, shift your body weight back and forth gently pulling the lever out away from the chair. This puts the chair into a free float/recline function. To lock chair into upright position, move chair to its most forward position and push the lever in gently as you shift your body weight slightly forward and backward. The lever will lock chair back to upright position.

B. Seat Height Adjustment

To lower seat height, pull the lever toward the seat while seated in the chair. To raise the seat, lift body weight slightly off chair while pulling the lever toward the seat. Release lever to lock in position.

C. Tilt Tension Adjustment

To adjust chair's tilt tension, locate the hand knob on the front of the mechanism. While seated in the chair turn the hand knob clockwise to increase tension. Turn the hand knob counterclockwise to decrease tension.

D. Back Height Adjustment

To adjust back height, grasp chair back and lift to desired height. The back will lock at each click stop. To lower back, simply raise above last click stop, disengaging the ratchet mechanism, and lower back to lowest position. Raise back height to desired position.

Fully Adjustable Arm Option

E. Arm Width Adjustment

To adjust arm width, pull up on lever moving arm horizontally in or out to one of three adjustment settings. Release lever to lock in place.

F. Arm Height Adjustment

To adjust arm height, pull up on button located at the top of the arm assembly. Raise or lower arm to the desired height and release lever to lock in position.

